


SISTEMA STIRANTE CON CALDAIA IN PRESSIONE
IRONING SYSTEM WITH PRESSURIZED BOILER
CENTRALE DE REPASSAGE AVEC CHAUDIÈRE SOUS
PRESSION
ΑΤΜΟΣΥΣΤΗΜΑ ΜΕ ΛΕΒΗΤΑ ΥΠΟ ΠΙΕΣΗ



Istruzioni per l'uso
Instructions for use
Mode d'emploi
Οδηγίες χρήσης






FIG. 4

	GB	F	I	GR
●	Acetate, acrylic, nylon, polyester, rayon	Acétate, acrylique, nylon, polyester, rayonne	Acetato, acrilico, nylon, poliestere, rayon	Συνθετικά, Ακρυλικά, Νάιλον, Πολυέστερ, Ραιγιόν
●●	Silk	Soie	Seta	Μεταξωτά
●● ☼	Wool, cotto, fine linen	Laine, coton, lin fin	Lana, cotone, lino fino	Μαλλίνα, βαμβακερά λεπτά, λινά
●●● ☼	Cotton, linen, starched, clothes	Coton, lin, tissus humectés amidonnés	Coton, lino, tessuti inamidati	Βαμβακερά, λινά, βρεγμένα υφάσματα

ELECTRICAL CONNECTION (UK ONLY)

- A) If your appliance comes fitted with a plug, it will incorporate a 13 Amp fuse. If it does not fit your socket, the plug should be cut off from the mains lead, and an appropriate plug fitted, as below.
WARNING: Very carefully dispose of the cut off plug after removing the fuse: do not insert in a 13 Amp socket elsewhere in the house as this could cause a shock hazard.
 With alternative plugs not incorporating a fuse, the circuit must be protected by a 15 Amp fuse.

WARNING - THIS APPLIANCE MUST BE EARTHED IMPORTANT


The wires in the mains lead are coloured in accordance with the following code:

Green and yellow: Earth
 Blue: Neutral
 Brown: Live



- If the plug is a moulded-on type, the fuse cover must be re-fitted when changing the fuse using a 13 Amp Asta approved fuse to BS 1362. In the event of losing the fuse cover, the plug must NOT be used until a replacement fuse cover can be obtained from your nearest electrical dealer. The colour of the correct replacement fuse cover is that as marked on the base of the plug.
- B) If your appliance is not fitted with a plug, please follow the instructions provided below:

As the colours of the wires in the mains lead may not correspond with the coloured markings identifying the terminals in your plug, proceed as follows:

The green and yellow wire must be connected to the terminal in the plug marked with the letter E or the earth symbol  or coloured green or green and yellow.

The blue wire must be connected to the terminal marked with the letter N or coloured black.

The brown wire must be connected to the terminal marked with the letter L or coloured red.

